

MGG Punktlichtlampen / MGG Point Light Lamps

Drahtenden Wire Terminals

	A Drahtlampe Standard-Type Wire Terminal Standard Type	B Linsen-Type Lens Type - 2 mm -	C Linsen-Type Lens Type - 3 mm -	D Linsen-Type Lens Type - 4 mm -					
Zeile Line	Nenn- spannung DesignVolts	Nennstrom Design Amps	Lichtstärke Candle Power	Lebensdauer (AC) Life (AC)	Wendel- aufbau Filament				
No.	[V]	[mA]	[MSCP]	[h]					
1	5,0	300	0,120	100.000	C-6	8008-70			
2	5,0	300	0,450	25.000	C-6	8019-70			
3	5,0	775	0,850	50.000	C-6(A)	8155-70	8163-80	8002-80	8018-80
4	5,0	775	1,432	10.000	C-6(A)	8009-70	8003-80	8011-80	8005-80
5	6,0	1.660	8,700	500	C-6(A)	8014-70	8166-80	8016-80	8069-80

Sockel 1/2-20UNF-2A Base 1/2-20UNF-2A

	E Standard-Type mit Sockel Standard Type with Base	F Linsen-Type Lens type - 2 mm - mit Sockel with Base	G Linsen-Type Lens type - 3 mm - mit Sockel with Base	H Linsen-Type Lens type - 4 mm - mit Sockel with Base					
Zeile Line	Nenn- spannung DesignVolts	Nennstrom Design Amps	Lichtstärke Candle Power	Lebensdauer (AC) Life (AC)	Wendel- aufbau Filament				
No.	[V]	[mA]	[MSCP]	[h]					
6	5,0	300	0,120	100.000	C-6	8013-72			
7	5,0	300	0,450	25.000	C-6	8029-72			
8	5,0	775	0,850	50.000	C-6(A)	8161-72	8167-82	8001-82	8022-82
9	5,0	775	1,432	10.000	C-6(A)	8010-72	8004-82	8012-82	8006-82
10	6,0	1.660	8,700	500	C-6(A)	8015-72	8170-82	8017-82 *	8023-82 *

Zylinder-Sockel / 12,5 mm Cylindrical Base / 12.5 mm

	I Standard-Type mit Sockel Standard Type with Base	J Linsen-Type Lens type - 2 mm - m.Sockel/w.Base Ø 12,5 mm	K Linsen-Type Lens type - 3 mm - m.Sockel/w.Base Ø 12,5 mm	L Linsen-Type Lens type - 4 mm - m.Base/w.Base Ø 12,5 mm					
Zeile Line	Nenn- spannung DesignVolts	Nennstrom Design Amps	Lichtstärke Candle Power	Lebensdauer (AC) Life (AC)	Wendel- aufbau Filament				
No.	[V]	[mA]	[MSCP]	[h]					
11	5,0	300	0,120	100.000	C-6	8075-72			
12	5,0	300	0,450	25.000	C-6	8080-72			
13	5,0	775	0,850	50.000	C-6(A)	8162-72	8164-82	8076-82	8077-82
14	5,0	775	1,432	10.000	C-6(A)	8007-72	8079-82	8024-82	8028-82
15	6,0	1.660	8,700	500	C-6(A)	8078-72	8168-82	8020-82 *	8070-82 *

Sockel (Abb. E-L) mit AMP-Flachstecker 2,8x0,8 mm (DIN 46330) für Flachsteckhülse -> MGG 20134-78.
Base (Fig. E-L with AMP-taps 2.8x0.8 mm (DIN 46330) for receptacle -> MGG 20134-78.