

T-1 1/2 TL-1 1/2

Zeile Line	Nenn- spannung DesignVolts	Nennstrom Design Amps	Lichtstärke Candle Power	Lebensdauer (AC) Life (AC)	Wendel- aufbau Filament	A Drahtlampe Wire Terminal	B Drahtlampe mit Linse Wire Terminal with Lens	C Schraubsockel Midget-Screw-Base E5/8 (L.E.S)	D Schraubsockel mit Linse Midget-Screw-Base with Lens E5/8 (L.E.S)
No.	[V]	[mA]	[MSCP]	[h]					
1	2,5	200	0,250	2.000	C-2R	6190-00	6454-10	6189-08	6358-18
2	2,5	300	0,500	500	C-2R	6660-00		6661-08	
3	2,5	350	0,200	15.000	C-2R	6008-00	6008-10	6008-08	6008-18
4	2,7	70	0,040	6.000	C-6	6277-00		6278-08	
5	3,5	160	0,080	15.000	C-2R	6351-00		6352-08	
6	4,0	50	0,020	20.000	C-2R	6405-00		6406-08	
7	4,5	60	0,100	4.000	C-2R	6669-00		6670-08	
8	5,0	60	0,050	100.000	C-2R	6560-00		6570-08	
9	5,0	115	0,150	40.000	C-2R	6511-00		6521-08	
10	5,0	300	0,950	400	C-2R	6004-00	6004-10	6004-08	6004-18
11	6,0	30	0,020	10.000	C-6	6603-00		6604-08	
12	6,0	40	0,030	15.000	C-2R	6696-00		6697-08	
13	6,0	60	0,120	8.000	C-2R	6672-00		6673-08	
14	6,0	80	0,070	60.000	C-2R	6608-00		6609-08	
15	6,0	80	0,090	35.000	C-2R	6618-00		6619-08	
16	6,0	80	0,110	20.000	C-2R	6628-00		6629-08	
17	6,0	100	0,120	40.000	C-2R	6610-00		6611-08	
18	6,0	165	0,300	15.000	C-2R	6616-00		6617-08	
19	6,0	200	0,600	3.000	C-2R	6192-00	6468-10	6191-08	6359-18
20	6,5	150	0,500	2.000	C-2R	6675-00		6674-08	
21	12,0	30	0,050	7.500	C-2F	6123-00		6124-08	
22	12,0	30	0,100	2.000	CC-6	6133-00		6134-08	
23	12,0	40	0,030	25.000	C-2F	6130-00		6140-08	
24	12,0	40	0,090	8.000	C-2F	6131-00		6141-08	
25	12,0	50	0,120	10.000	C-2F	6125-00		6126-08	
26	12,0	60	0,150	20.000	C-2F	6135-00		6136-08	
27	12,0	80	0,200	25.000	C-2F	6678-00		6679-08	
28	12,0	83	0,300	10.000	C-2F	6002-00		6002-08	
29	12,0	90	0,250	20.000	C-2F	6129-00		6139-08	
30	12,0	100	0,250	35.000	C-2F	6121-00		6122-08	
31	14,0	40	0,150	5.000	C-2F	6689-00		6690-08	
32	16,0	50	0,200	8.000	C-2F	6253-00		6254-08	
33	18,0	40	0,150	7.000	C-2F	6683-00		6684-08	
34	24,0	35	0,150	7.000	C-2F	6243-00		6244-08	
35	24,0	40	0,150	10.000	C-2F	6686-00		6687-08	
36	24,0	40	0,250	5.000	C-2F	6240-00		6241-08	
37	24,0	50	0,500	1.000	C-2F	6235-00		6235-08	
38	28,0	40	0,340	5.000	C-2F	6194-00	6363-10	6193-08	6364-18

Verwendbare Fassungen/applicable lampholder:
Spalte/column C+D = MGG 20170-47